

CHALK—BOARD APPLICATION INSTRUCTIONS

The chalkboard application is basically just a “PEEL and STICK”.

1. Remove just HALF of the white backing paper and hold up the chalkboard to the wall—adjusting the position if necessary before letting the ‘sticky side’ touch the wall.
2. Once you are happy with the position, smooth down the exposed/sticky side onto the wall and carefully peel back the remaining white backing paper.
3. Rub over the entire surface with a spatula or credit card to smooth out any bubbles and help the adhesive to stick to the wall.
4. Slowly peel back the top layer of transfer tape—(if tape has been applied—) to reveal the chalkboard surface.
5. Write your messages using regular chalk or chalk markers*. A damp cloth works well for erasing the chalk for a ‘clean slate’.

**when purchasing ‘chalk markers’ - avoid ‘PAPERMATE’ brand. They don’t seem to be compatible with our chalkboard vinyl.*

The chalkboard vinyl can be repositioned*—but if it has small pieces cut out—that may make it more difficult to reposition. **Note: chalkboard vinyl can be repositioned on walls only. Smoother surfaces such as glass or stainless steel surfaces don’t allow for repositioning.*



WordPlay Designs is not liable for any surface damage from application or removal of vinyl. No refunds on items that have been used.